

**Podatkovna kartica po uredbi 65/2014 / Fiche for domestic range hoods regulation 65/2014**

Ime dobavitelja ali blagovna znamka / Name or trade mark	<b>ETIS</b>
Oznaka ali model / Model identifier	<b>DAH 906 IX</b>
Letna poraba energije (AEC <sub>napa</sub> ) v kWh/leto / Annual Energy Consumption (AEC <sub>hood</sub> ) in kWh/a	<b>97</b>
Razred Energetske učinkovitosti / Energy Efficiency class	<b>E</b>
Učinkovitost pretoka zraka (FDE <sub>napa</sub> ) / Fluid Dynamic Efficiency (FDE <sub>hood</sub> )	<b>5,5</b>
Razred Učinkovitosti pretoka zraka / Fluid Dynamic Efficiency class	<b>F</b>
Učinkovitost osvetljevanja (LE <sub>napa</sub> ) v lux/watt / Lighting Efficiency (LE <sub>hood</sub> ) in lux/Watt	<b>2</b>
Razred učinkovitosti osvetljevanja / Lighting Efficiency class	<b>G</b>
Učinkovitost filtriranja maščob / Grease Filtering Efficiency	<b>76,1</b>
Razred učinkovitosti filtriranja maščob / Grease Filtering Efficiency class	<b>C</b>
Pretok zraka v m <sup>3</sup> /h pri najnižji stopnji / Air flow at minimum speed in m <sup>3</sup> /h	<b>186</b>
Pretok zraka v m <sup>3</sup> /h pri najvišji stopnji (intenzivno ali pospešeno sta izključeni) / Air flow at maximum speed in normal use, intensive or boost excluded m <sup>3</sup> /h	<b>258</b>
Pretok zraka v m <sup>3</sup> /h pri intenzivni ali pospešeni nastaviti / Air flow at intensive or boost setting in m <sup>3</sup> /h	-
Zračne akustične A-utežene emisije zvokovne moči pri najnižji in najvišji hitrosti pri običajni rabi, izračeno v dB / Airborne acoustical A-weighted sound power emissions at minimum and maximum speed available in normal use in dB	<b>53/61</b>
Zračne akustične A-utežene emisije zvokovne moči pri intenzivni ali pospešeni stopnji, izraženo v dB / Airborne acoustical A-weighted sound power emissions at intensive or boost setting in dB	-
Zahtevana moč v stanju izključenosti (P <sub>o</sub> ) v Watt-ih / Power consumption in off mode (P <sub>o</sub> ) in Watt	<b>0</b>
Zahtevana moč v stanju pripravljenosti (P <sub>s</sub> ) v Watt-ih / Power consumption in standby mode (P <sub>s</sub> ) in Watt	-

**Tehnična dokumentacija po uredbi 66/2014 / Technical documentation for domestic range hoods regulation 65/2014**

Ime dobavitelja ali blagovna znamka / Name and address of the supplier	<b>ETIS d.o.o., Tržaška cesta 553, SI-1000 Ljubljana</b>
Oznaka ali model / Model identifier	<b>DAH 906 IX</b>
Indeks energetske učinkovitosti EEI <sub>napa</sub> / Energy Efficiency Index (EEI <sub>hood</sub> )	<b>104,2</b>
Razred energetske učinkovitosti / Energy Efficiency class	<b>E</b>
Letna poraba energije AEC <sub>napa</sub> / Annual Energy Consumption (AEC <sub>hood</sub> )	<b>97</b>
Faktor povečanja časa (f) / Increase factor (f)	<b>1,8</b>
Učinkovitost pretoka zraka FDE <sub>napa</sub> / Fluid Dynamic Efficiency (FDE <sub>hood</sub> )	<b>5,5</b>
Razred učinkovitosti pretoka zraka FDE <sub>napa</sub> / Fluid Dynamic Efficiency class	<b>F</b>
Pretok v kuhinjski napi na točki najvišje učinkovitosti Q <sub>BEP</sub> , m <sup>3</sup> /h / Measured flow rate of the domestic range hood at the best efficiency point (Q <sub>BEP</sub> ) in m <sup>3</sup> /h	<b>121</b>
Vrednost razlike statičnega tlaka kuhinjske nape na točki navečje učinkovitosti P <sub>BEP</sub> , Pa / measured value of the static pressure difference of the domestic range hood at the best efficiency point (P <sub>BEP</sub> ) in Pa	<b>140</b>
Vrednost vhodne električne moči kuhinjske nape na točki največje učinkovitosti W <sub>BEP</sub> v Watt-ih / Measured value of the electric power input of the domestic range hood at the best efficiency point (W <sub>BEP</sub> ) in Watt	<b>85</b>
Povprečna osvetljenost kuhalne površine E <sub>povprečna</sub> v Luksih / Average illumination of the lighting system on the cooking surface (E <sub>middle</sub> ) in lux	<b>96</b>
Nazivna vhodna moč sistema osvetljevanje kuhalne površine W <sub>L</sub> v Watt-ih / Nominal power consumption of the lighting system on the cooking surface (W <sub>L</sub> ) in Watt	<b>56</b>
Učinkovitost osvetljevanja LE <sub>napa</sub> v Luks/watt / Measured value of the Lighting Efficiency (LE <sub>hood</sub> )	<b>2</b>
Razred učinkovitosti osvetljevanja / Lighting Efficiency class	<b>G</b>
Izmerjena vrednost učinkovitosti filtriranja maščob GFE <sub>napa</sub> / Measured value of the Grease Filtering Efficiency (GFE <sub>hood</sub> )	<b>76,1</b>
Razred učinkovitosti filtriranja maščob / Grease Filtering Efficiency class	<b>C</b>
Zahtevana moč v stanju izključenosti P <sub>o</sub> v Watt-ih / Power consumption in off mode (P <sub>o</sub> ) in Watt	<b>0</b>
Zahtevana moč v stanju pripravljenosti P <sub>s</sub> v Watt-ih / Power consumption in standby mode (P <sub>s</sub> ) in Watt	-
Zračne akustične A-utežene emisije zvokovne moči pri najnižji in najvišji hitrosti pri običajni rabi, izračeno v dB / Airborne acoustical A-weighted sound power emissions at minimum and maximum speed available in normal use, in dB	<b>53/61</b>
Zračne akustične A-utežene emisije zvokovne moči pri intenzivni ali pospešeni stopnji, izraženo v dB (če je navoljo) / Airborne acoustical A-weighted sound power emissions at intensive or boost setting, in dB ( if present )	-
Vrednost pretoka zraka pri najnižji in najvišji hitrosti pri običajni rabi v m <sup>3</sup> /h / Air flow values of the domestic range hood at minimum and maximum speed available in normal use in m <sup>3</sup> /h	<b>186/258</b>
Vrednost pretoka zraka pri intenzivni ali pospešeni rabi v m <sup>3</sup> /h ( če je navoljo ) / Air flow value of the domestic range hood at intensive or boost setting in m <sup>3</sup> /h ( if present )	-

Informacije o izdelku po direktivi 66/2015 /Information for domestic range hoods regulation EU 66/2015	Oznaka/Symbol	Vrednost/Value	Enota/Unit
Oznaka modela / Model identification			<b>DAH 906 IX</b>
Letna porava energije / Annual Energy Consumption	AEC <sub>napa</sub> / AEC <sub>hood</sub>	<b>97</b>	kWh/a
Faktor povečanja časa / Time increase factor	f / f	<b>1,8</b>	
Učinkovitost pretoka zraka / Fluid Dynamic Efficiency	FDE <sub>napa</sub> /FDE <sub>hood</sub>	<b>5,5</b>	
Indeks energijske učinkovitosti pretoka zraka / Energy Efficiency Index	EEI <sub>napa</sub> /EEI <sub>hood</sub>	<b>104,2</b>	
Izmerjena stopnja pretoka zraka na točki najvišje učinkovitosti/Measured air flow rate at best efficiency point	Q <sub>BEP</sub> /Q <sub>BEP</sub>	<b>121,0</b>	m <sup>3</sup> /h
Izmerjen zračni tlak na točki največje učinkovitosti / Measured air pressure at best efficiency point	P <sub>BEP</sub> /P <sub>BEP</sub>	<b>140</b>	Pa
Največji pretok zraka / Maximum air flow	Q <sub>max</sub> /Q <sub>max</sub>	<b>258</b>	m <sup>3</sup> /h
Izmerjena vhodna električna moč točki največji na točki največje učinkovitosti / Measured electric power input at best efficiency point	W <sub>BEP</sub> /W <sub>BEP</sub>	<b>85,0</b>	W
Nazivna moč sistema za osvetljevanje / Nominal power of the lighting system	W <sub>L</sub> /W <sub>L</sub>	<b>56,0</b>	W
Povprečna osvetljenost kuhalne površine ki jo zagotavlja sistem za osvetljevanje / Average illumination of the lighting system on the cooking surface	E <sub>povprečna</sub> /E <sub>middle</sub>	<b>96</b>	luks/lux
Izmerjena zahtevana moč v stanju pripravljenosti / Measured power consumption in standby mode	P <sub>s</sub> /P <sub>s</sub>	-	W
Izmerjena zahtevana moč v stanju izključenosti / Measured power consumption off mode	P <sub>o</sub> /P <sub>o</sub>	<b>0</b>	W
Nivo zvokovne moči / Sound power level	L <sub>WA</sub> /L <sub>WA</sub>	<b>61</b>	dB